Search Query Case No. 10/720,796

1	("6181456").PN.	USPAT
1	("6449080").PN.	USPAT
1	("5214724").PN.	USPAT
1	("6449080").PN.	USPAT
0	(("6449080").PN.) and (high with frequency)	USPAT
0	(("6449080").PN.) and capacitor$1	USPAT
11954	interdigitate$1	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
3177	interdigitate$1 with electrode$1	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
200	interdigitate$1 with electrode$1 with capacitor$1	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
7	interdigitate$1 with ground with electrode$1 with capacitor$1	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
1	("4410905").PN.	USPAT
0	(("6449080").PN.) and (high with frequenc$3)	USPAT
11	slot$3 with ground$3 with electrode$1 with capacitor$1	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
366	ground$3 with electrode$1 with capacitor$1 with high with frequenc$3	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
429	ground$3 with electrode$1 with capacit$3 with high with frequenc$3	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
0	slot$3 with ground$3 with electrode$1 with capacit$3 with high with frequenc$3	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
13	structure$1 with ground$3 with electrode$1 with capacit$3 with high with frequenc$3	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
79	coupl$4 with ground$3 with electrode$1 with capacit$3 with high with frequenc$3	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
33	coupl$4 with (ground$3 near2 electrode$1) with capacit$3 with high with frequenc$3	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
32	coupl$4 with (ground$3 near2 electrode$1) with capacit$3 with (high adj frequenc$3)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
5	(ground$3 near2 electrode$1) with (capacitive adj coupling) with (high adj frequenc$3)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
0	(comb$3 with electrode$1) with (capacitive adj coupling) with (high adj frequenc$3)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB

4	(structure$1 with electrode$1) with (capacitive adj coupling) with (high adj frequenc$3)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
0	electrode$1 with (capacit$3 adj structure$1) with coupl$3 with (high adj frequenc$3)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
16	electrode$1 with (capacit$3 with structure$1) with coupl$3 with (high adj frequenc$3)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
1	(("6449080").PN.) and (thermal adj stress)	USPAT
1	(("6449080").PN.) and (slot$3 with (thermal adj stress))	USPAT
1	(("6449080").PN.) and (width with ground with rf)	USPAT
1	(("6449080").PN.) and (width with ground with rf with slot$3)	USPAT
1	(("6449080").PN.) and (width with slot$3)	USPAT
2225	(359/237,245,254,315,322).CCLS.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
9171	(385/1-4,8,9,14,15,27,39,40).CCLS.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
133	(334/45).CCLS.	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
11256	((359/237,245,254,315,322).CCLS.) or ((385/1-4,8,9,14,15,27,39,40).CCLS.) or ((334/45).CCLS.)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
7	(((359/237,245,254,315,322).CCLS.) or ((385/1-4,8,9,14,15,27,39,40).CCLS.) or ((334/45).CCLS.)) and (second adj waveguide$1) and (slot$3 with electrode$1)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB